



BRIM is a professional downlight with high lumen output, compact and elegant design. Unique structure of interchangeable reflector, excellent heat dissipation performance. Thanks for the new technology of dark light reflector, which makes it can deliver a very soft and glare-free lighting effect. IP65 rated version make it more stronger and wider use in an tough environment.

Die-casting aluminium housing.

Powdercoating finish.

Excellent anti-glare control.


With both optical lens and high purity aluminium reflector can achieve a perfect lighting solution.

No UV or IR, can protect commodities properly, to avoid the color fading from radiation.

LED driver is connected externally.

Easy for installation and maintenance.

Suitable for 8-30mm different thickness of ceiling type.



Product Description:

Ref.No	Watts (W)	Beam angle (°)	Output Lumens (lm)	CCT (K)	Input Voltage (AC V)	CRI (Ra)	Weight (KG)
81554608	20	18	1680	3000/4000	220-240 50HZ/60HZ	>80	1.0
81554618	20	24	1670	3000/4000	220-240 50HZ/60HZ	>80	1.0
81554628	20	36	1630	3000/4000	220-240 50HZ/60HZ	>80	1.0
81554808	26	18	1950	3000/4000	220-240 50HZ/60HZ	>80	1.0
81554818	26	24	1950	3000/4000	220-240 50HZ/60HZ	>80	1.0
81554828	26	36	1900	3000/4000	220-240 50HZ/60HZ	>80	1.0
81554838	30	18	2300	3000/4000	220-240 50HZ/60HZ	>80	1.0
81554848	30	24	2300	3000/4000	220-240 50HZ/60HZ	>80	1.0
81554858	30	36	2250	3000/4000	220-240 50HZ/60HZ	>80	1.0
81554638	34	18	2650	3000/4000	220-240 50HZ/60HZ	>80	1.0
81554648	34	24	2650	3000/4000	220-240 50HZ/60HZ	>80	1.0
81554658	34	36	2580	3000/4000	220-240 50HZ/60HZ	>80	1.0

* Ra90 or above is on request.

* Other CCT are available upon request.

* Lumen output is concerned with different CCT.

Accessories



Glossy reflector
10501814





Satin reflector
10501810



Mat black reflector
10501812



Mat white reflector
10501813



*IES files of different beam angle are available upon request.