

Ref.No	A	B
83052820	140	250
83052830	140	250
83052832	140	250
83052858	140	180
83052848	140	180
83052838	140	180
83052878	140	180
83052888	140	180
83052868	140	180
83053260	140	180
83053270	140	260
83053280	140	260
83053290	140	300

Cylinder surface mounted downlight with high protection mode, it is suitable for the transitional areas between indoors and outdoors. Typically they are used for balconies, porches, cantilevered roofs and covered terraces and etc...

Die-casting aluminium housing with powdercoating finish.

High purity anodized aluminum reflector, minimized the anti-glare efficiently. With glass diffuser.

Screw-less front cover.

Built-in ballast.

Easy for installation and maintenance.

Product Description:



Ref.No	Watts (W)	Beam angle (°)	Output Lumens (lm)	CCT (K)	Input Voltage (AC V)	CRI (Ra)	Weight (KG)
83052820	35	14	2210	3000/4200	220-240 50HZ/60HZ	>80	2.55
83052830	35	24	2470	3000/4200	220-240 50HZ/60HZ	>80	2.55
83052832	35	42	2340	3000/4200	220-240 50HZ/60HZ	>80	2.55







Ref.No	Watts (W)	Beam angle (°)	Output Lumens (lm)	CCT (K)	Input Voltage (AC V)	CRI (Ra)	Weight (KG)
83052858	15	24	1000	3000/4000	220-240 50HZ/60HZ	>80	1.95
83052848	15	36	1000	3000/4000	220-240 50HZ/60HZ	>80	1.95
83052838	15	60	1000	3000/4000	220-240 50HZ/60HZ	>80	1.95
83052878	20	24	1350	3000/4000	220-240 50HZ/60HZ	>80	1.95
83052888	20	36	1350	3000/4000	220-240 50HZ/60HZ	>80	1.95
83052868	20	60	1350	3000/4000	220-240 50HZ/60HZ	>80	1.95
83053260	26	12/24/36/60	1650	3000/4000	220-240 50HZ/60HZ	>80	1.95
83053270	30	12/24/36/60	1850	3000/4000	220-240 50HZ/60HZ	>80	2.3
83053280	34	12/24/36/60	2100	3000/4000	220-240 50HZ/60HZ	>80	2.3
83053290	38	12/24/36/60	2300	3000/4000	220-240 50HZ/60HZ	>80	2.5

* Ra90 or above is on request.

* Other CCT are available upon request.

* Lumen output is concerned with different CCT.



*IES files of different beam angle are available upon request.