



Mini LED inground light is with simple & elegant design, high efficiency with excellent glare control. Using CREE single LED, different beam angle of optical lens are optional from narrow beam to flood beam, different power and CCT are available. It's widely used for plaza, park, shopping center, path, courtyard as well as the highlight of sculpture decoration & outdoor wall etc...

Die-casting aluminium housing & 304# stainless steel frame.
Use M5 stainless screw to fix the pre-buried box.

No UV or IR.

12mm safety tempered glass, silicon gasket.


Built-in driver.

Loading weight : 1000Kg(5km/h).

Surface temperature ≤ 60°.

Installation way: with pre-buried box.

Adjustable angle: ±20°.



Product Description:

Ref.No	Watts (W)	Beam angle (Δ°)	Output Lumens (lm)	CCT (K)	Input Voltage (DC V)	CRI (Ra)	Weight (KG)
85021418	3x1	15	180	3000/4000	24	≥80	1.3
85021428	3x1	20	180	3000/4000	24	≥80	1.3
85021438	3x1	30	180	3000/4000	24	≥80	1.3
85021458	3x1	40	180	3000/4000	24	≥80	1.3
85021468	3x2	15	350	3000/4000	24	≥80	1.3
85021478	3x2	20	350	3000/4000	24	≥80	1.3
85021488	3x2	30	350	3000/4000	24	≥80	1.3
85021498	3x2	40	350	3000/4000	24	≥80	1.3


Accessories





Asymmetrical glass
20410064040B00



pre-buried box



* Ra90 or above is on request.
* Other CCT are available upon request.
* Lumen output is concerned with different CCT.



*IES files of different beam angle are available upon request.